



Agip BLASIA

High-pressure gear oil based on mineral oil for oiltight mechanical industrial transmissions and other high loaded lubricating points.

Characteristics (typical figures):

Agip BLASIA	Unit	68	100	150	220	320	460	680	Test method
Kin. Viscosity at 40°C	mm ² /s	64	99	141	220	303	461	628	DIN 51 550
	at 100°C	mm ² /s	8,4	11,1	14,1	18,9	23,4	30,5	
Viscosity index		98	96	96	96	96	95	95	DIN ISO 2909
Density at 15°C	kg/m ³	885	890	895	900	903	909	915	DIN 51 757
Flashpoint o. C.	°C	225	228	238	240	240	245	250	DIN ISO 2592
Pour point	°C	-24	-24	-21	-18	-18	-15	-9	DIN ISO 3016
Designation		CLP	CLP	CLP	CLP	CLP	CLP	CLP	DIN 51 517 T.3
ISO-VG grades		68	100	150	220	320	460	680	

Properties and Performance:

Agip BLASIA - types are produced from a well-balanced combination of carefully selected base oils and coordinated high-pressure additives with them with a wide sphere of action. Sulphurous additives cause at relatively high gliding speeds as well as well as at intermittent and oscillating loads a layer building stable lubrication film. Additives based on phosphor take effect especially at high loaded slow running transmissions and contribute the formation of a stable and seizing preventing lubrication film. The high base oil quality in connection with oxidation inhibitors ensure a high thermal load capacity and long service times. They are compatible with all common sealing materials and internal varnishes.

Applications:

Agip BLASIA - types are applicable as high-performance gear oils for the splash and circular lubrication in all oiltight incased transmissions, especially with mechanically high loaded lubricating points such as slow running and high loaded sliding and roller bearings, clutches, spindles and transmissions with high surface pressures and numbers or revolution. Since these oils do not content lead soaps they can also be used for the oil mist lubrication.

Please observe the manufacturer's specifications when selecting products!



Agip BLASIA

Additional physical-technical data:

Agip BLASIA	Unit	68	100	150	220	320	460	680	Test method	
Neutralisation number (s)	mgKOH/g	0,4	0,5	0,5	0,5	0,5	0,6	0,6	DIN 51 558 T.1	
Ash (sulphate)	weight %	0,04								DIN 51 575
Coke residue according to Conradson	weight %	0,1	0,1	0,3	0,4	0,5	0,7	1,5	DIN 51 551	
Corrosion effect on copper	Corr.-grade	1 - 100 A 3								DIN 51 759
Corrosion protection properties against steel	Corr.-grade	0 - A								DIN 51 355 method A
Determination of undissolved materials	g/100 g	< 0,03								DIN 51 592
Demulsifying power	54°C	min	15	10	---	---	---	---		
	82°C	min			15	15	15	15	---	DIN 51 599
Water content	g/100g	< 0,1								DIN ISO 3733
FZG-Test A/16,6/140 load stage		> 12								DIN 51 354 T.2
Spec. change of weight	mg/KWh	< 0,27								
Timken test OK load	lbs	60	60	60	65	60	65	65		

Specifications:

DIN 51 517 T.3 (CLP)
Thyssen TH-N 256 142
CINCINNATI MILACRON P63 (68), P77 (150), P74 (220), P35 (460)