

# Balmerol<sup>®</sup> Slipcoat

## High Performance Pre-Coat Launching Grease

Technical Data Sheet

### Product Description / Application:

Balmerol Slipcoat is water resistant grease. When applied over a foundation layer of Balmerol Basecoat, forms a friction-reducing surface, which permits the smooth control of launching a ship from shore to water.

The thickness of Balmerol Slipcoat is maintained in such a way that it ensures easy application and also resists excessive displacement of it under extreme loads encountered during launching.

### Typical Properties:

Balmerol Slipcoat	
Properties	Typical Value
Base	Lithium
Colour, Visual	Dark
Texture	Smooth Mass
Worked Penetration 60/60 strokes at 25°C, ASTM D 217	265 - 295
Drop Point, ASTM D 566	180

### Health and Safety:

Balmerol Slipcoat is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. For MSDS please contact your local Balmer Lawrie Marketing / Technical Service team.

For Further Information, contact:

**Balmer Lawrie & Co. Ltd.**  
SBU: Greases & Lubricants (G&L) Division  
P- 43, Hide Road Extension  
Kolkata: 700088  
www.balmerlawrie.com